



NOTES

- ① ROMAC PART# S11-3.50 X 3.50 X 7SSFE WITH NBR GASKETS
- ② 3" X 32" PIPE (ONE END THREADED)
- ③ 3" X 3" X 3" THREADED TEE (150psi)
- ④ 3" X 7-1/4" PIPE (BOTH ENDS THREADED)
- ⑤ 3" S.S. STREAM FLOW BALL VALVE MODEL BV150SS3FP S.S. FULL PORT S.S. BALL VALVE THREADED HANDLE CUT TO FIT MAXIMUM CLEARANCE 1" REMOVE LATCH LOCK
- ⑥ 3" X 4" NIPPLE (BOTH ENDS THREADED)
- ⑦ 3" CAM & GROOVE MALE ADAPTOR BY 3" MALE N.P.T. (BRASS)
- ⑧ 3" CAM & GROOVE DUST CAP (BRASS)

NOTES:

BALL VALVES AND TEE ASSEMBLIES ARE VERTICAL TO LPFM BUT ARE SHOWN HORIZONTAL FOR CLARITY

SEE COUPLING DETAIL FOR ALL ROMAC COUPLING POSITIONS

FOR A SMALLER SIDELINE SEE LPFM26 & LPFM27 DRAWINGS.

GENERAL NOTES:

- ALL MATERIALS MUST BE 304 STAINLESS STEEL SCHEDULE 40 (EXCEPT AS NOTED)

EXPLODED TOP VIEW
NOT TO SCALE

THE
METROPOLITAN SEWER DISTRICT
OF
GREATER CINCINNATI

**3" LOW PRESSURE FORCE MAIN
RIGHT TEE FLUSHING CHAMBER DETAIL**